

FlexPAC I 730

Highly configurable, rugged portable



The ideal cost-effective, highly versatile rugged portable solution

The FlexPAC I 730 is a robust, lunchbox computer that is built using heavy-duty metal. It is a tough, go-anywhere unit ideally suitable for harsh/severe environments and mission-critical applications. With passive backplane board configurations to choose from, the available full-length expansion slots of the FlexPAC I 730 can be freely configured with other uniquely designed expansions cards for most applications.

In addition, the 17.3" HD LCD display of the FlexPAC I 730 is guarded with a specially designed anti-glare tempered glass for added protection. Every unit comes equipped with dual system cooling side fans and easy access to its expansion ports for immediate system upgrade or maintenance. Functional practicality combined with its elegantly simple and polished design, the extra-rugged FlexPAC I is the most cost-effective, durable and efficient portable solution for your mission-critical applications.

Technical Specifications		
Product Name	FlexPAC I 730	
Diagonal	17.3", 16:9 Display	
LCD Resolution	1920 x 1080	
CPU	Intel® Core™ i7-4930K Processor (12M Cache, up to 3.90 GHz)	
Memory	32GB 1600MHz DDR3 Non-ECC Unbuffered Memory	
VGA	NVIDIA GeForce GTX 750 Ti GDDR5 2GB	
Slots	2x PCI-E 3.0 x16 slot 1x PCI-E 3.0 x4 (in x8) sot 1x PCI-E 2.0 x 4 (in x8) slot, 1x PCI-32 Slot	
Hard Drive Magazines	Option 1: Up to 18TB (18x 2.5" SSD) Option 2: Up to 24TB (6x 3.5" HDD) Option 3: Up to 36TB (18x 2.5" HDD)	
Brightness	300 cd/m2	
Contrast Ratio	1000:1	
Audio	7.1 High Definition Audio with S/PDIF header	
USB	4 USB 3.0 (5Gbps) ports (2 rear, 2 via header) & 14 USB 2.0 ports (8 rear, 6 via header)	
LAN	2x Gb Ethernet	
Power	650W PS2	
Dimensions/Weight	332mm x 433mm x 228mm (H x W x D) / 13.5 kgs N.W	
Environmental Specifications		
	Operating Temperature	Storage Temperature
System Temperature	-10°C to 50°C	-20°C to 70°C
Relative Humidity	10% to 90%	10% to 90%
Shock	10g, 11ms, Half-Sine	30g, 11ms, Half-Sine
Vibration	0.4Grms (10 to 500Hz)	1.12Grms (10 to 500Hz)

System Includes:

- System components and parts
- Power cord with motherboard manual & driver
- Padded carrying bag with wheels
- Anti-static bag
- Pre-ship FQC checklist report

Optional:

- Military-Grade rugged case
- IP-rated, waterproof keyboards
- Sunlight readable
- Resistive and capacitive touch screens
- Hot-swappable batteries